

Filters for the T-630 with Perkins 1104D Tier III Engine & Stauff Filters						
	Stauff Filter for Hydrostatic Pump Suction	Stauff Filter for Auxillary Return - Twin Element	Enginaire Air Filter - www.enginaire.com	Engine Fuel	Engine Fuel/Water Separator	Engine Oil
Stauff	SF6707-MG	SF6707-MG				
Donaldson	P165762	P165762	NC	NC	P556245	P554407
Perkins			NC	2656F843	2656F853	2654407
Wix	51847	51847	NC	NC	NC	51459
Napa	1847	1847	NC	NC	NC	NC
Enginaire			68191-1			
Tucker	80101-2-01	80101-2-01	65575-01	65575-03	65575-04-1	65575-69
Change Hours	500	500	Reference Engine Manual			
NC = No Cross Reference Known at this time						
Wheel Gearbox	Change after first 50 hours, then yearly. Uses HD 80W-140 Gear Lubricant					

Filtros del T-630 con Motor Perkins 1104D Tier III & Stauff Filtros						
	Filtro Eaton para la succion de la Bomba Hydrostatica	Filtro Eaton Para Auxiliar Doble Elemento	Filtros de Aire- Enginaire www.enginaire.com	Combustible	Separador de Combustible/Agua	Aceite
Stauff	SF6707-MG	SF6707-MG				
Donaldson	P165762	P165762	NO	NO	P556245	P554407
Perkins			NO	2656F843	2656F853	2654407
Wix	51847	51847	NO	NO	NO	51459
Napa	1847	1847	NO	NO	NO	NO
Enginaire			68191-1			
Tucker	80101-2-01	80101-2-01	65575-01	65575-03	65575-04-1	65575-69
Cambio por Hora	500 hrs	500	Referirse al Manual del Motor			
NO = No tenemos referencias en estos momentos						
Nucleo de velocidades de la rueda trasera	Cambiar filtro despues de las primeras 50 horas, luego cada año. Usar el Lubricante HD 80W-140					

Filters for the T-630 with Perkins 1104D Tier III Engine & Eaton Filters						
	Eaton Filter for Hydrostatic Pump Suction	Eaton Filter for Auxillary Return - Twin Element	Enginaire Air Filter - www.enginaire.com	Engine Fuel	Engine Fuel/Water Separator	Engine Oil
Eaton	V0211B2R10	V0211B2R05				
Donaldson	P165876	P165762	NC	NC	P556245	P554407
Perkins			NC	2656F843	2656F853	2654407
Wix	51849	51847	NC	NC	NC	51459
Napa	1849	1847	NC	NC	NC	NC
Enginaire			68191-1			
Tucker	80107-1-01	80101-1-01	65575-01	65575-03	65575-04-1	65575-69
Change Hours	500	500	Reference Engine Manual			
NC = No Cross Reference Known at this time						
Wheel Gearbox	Change after first 50 hours, then yearly. Uses HD 80W-140 Gear Lubricant					

Filtros del T-630 con Motor Perkins 1104D Tier III & Eaton Filtros						
	Filtro Eaton para la succion de la Bomba Hydrostatica	Filtro Eaton Para Auxiliar Doble Elemento	Filtros de Aire- Enginaire www.enginaire.com	Combustible	Separador de Combustible/Agua	Aceite
Eaton	V0211B2R10	V0211B2R05				
Donaldson	P165876	P165762	NO	NO	P556245	P554407
Perkins			NO	2656F843	2656F853	2654407
Wix	51849	51847	NO	NO	NO	51459
Napa	1849	1847	NO	NO	NO	NO
Enginaire			68191-1			
Tucker	80107-1-01	80101-1-01	65575-01	65575-03	65575-04-1	65575-69
Cambio por Hora	500 hrs	500	Referirse al Manual del Motor			
NO = No tenemos referencias en estos momentos						
Nucleo de velocidades de la rueda trasera	Cambiar filtro despues de las primeras 50 horas, luego cada año. Usar el Lubricante HD 80W-140					

## Tuckerbilt® T-630 Filters:

Perkins 1104D Engine Tier III

	Spin On for Sunstrand Suction 10 Micron	Twin Elements 10 Micron	Engineaire Filter	Fuel	Fuel/Water Separator	Oil
Gresen	7520-001	3293-001	*NA	*NA	*NA	*NA
Donaldson	P550388	P553293			P556245	P554407
Perkins 1104D	*NA	*NA		2656F843	2656F501	2654407
Wix	51759	51506				51459
NAPA	1759	1506				
Twin Elements Flat Gasket Gresen #		1575-001				
Twin Elements 'O' Ring Gresen #		1576-001				

CAT 3054C / Perkins 1104C Engine Tier II

	Spin On for Sunstrand Suction 10 Micron	Twin Elements 10 Micron	Air	Fuel	Fuel/Water Separator	Oil
Gresen	7520-001	3293-001	*NA	*NA	*NA	*NA
Donaldson	P550388	P553293			P556245	P554407
Caterpillar 3054C	*NA	*NA	Inner: 233-5184 Outer: 233-5182	934-181	252-6338	7W-2326
Perkins 1104C	*NA	*NA	Inner: 26510381 Outer: 26510380	26560201	26550005	2654407
Wix	51759	51506				51459
NAPA	1759	1506				
Twin Elements Flat Gasket Gresen #		1575-001				
Twin Elements 'O' Ring Gresen #		1576-001				

\*NA Not Applicable

John Deere 4045T with TIER II Electronic Ignition

	Spin On for Sunstrand Suction 10 Micron	Twin Elements 10 Micron	Air	4045T Fuel	4045T Oil
Gresen	7520-001	3293-001	*NA	*NA	*NA
Donaldson	P550388	P553293	P181045		
John Deere	*NA	*NA	*NA	RE509031	RE504836
Wix	51759	51506	42234		
NAPA	1759	1506	2234		
Twin Elements Flat Gasket Gresen #		1575-001			
Twin Elements 'O' Ring Gresen #		1576-001			

John Deere 4045T prior to TIER II Electronic Ignition

	Spin On for Sunstrand Suction 10 Micron	Twin Elements 10 Micron	Air	4045T Fuel	4045T Oil
Gresen	7520-001	3293-001	*NA	*NA	*NA
Donaldson	P550388	P553293	P181045	P550351	P551352
John Deere	*NA	*NA	*NA	RE62418	RE59754
Wix	51759	51506	42234	33531	57243
NAPA	1759	1506	2234	3531	7243
Twin Elements Flat Gasket Gresen #		1575-001			
Twin Elements 'O' Ring Gresen #		1576-001			

\*NA Not Applicable